

PIPELIFE EASY LAY INSERTS – TECHNICAL DATA SHEET

1) Product Description

Pipelife Easy Lay PB Inserts which are orange in color and supplied in 10mm, 15mm, 22mm and 28mm sizes are manufactured from a high strength glass filled resin. Easy lay PB barrier pipes require internal support inserts to be fitted before insertion into a fitting. Pipelife Easy Lay inserts are suitable for hot and cold water distribution systems, underfloor heating systems and central / plumbing heating systems. Pipelife Inserts are designed to suit BS 7291 Pushfit fitting as well as standard brass compression fittings.

2) Certification

Pipelife Easy Lay Inserts are BS 7291 Class S Kitemark approved.
Pipelife Easy Lay Inserts are WRAS approved for drinking water applications.

3) Technical data

Content glass = > 30%
Flexural modulus > 6000MPa
Vicat B/120 > 150°C

4) Pipelife Easy Lay Inserts – applications classes and service conditions

Pipelife Inserts are manufactured and certified to the Class S service requirements of BS7291

5) Pipelife Easy Lay Insert guarantee

Pipelife Easy Lay Inserts are guaranteed for a period of: **50 years**



Provided Pipelife installation guidelines are adhered to, Easy Lay inserts are guaranteed against any manufacturing defects for a period of 50 years.

Paul Warren
Technical and Quality Control Dept.
20/03/21